

Wellhead Automation & Safety Panel

BLUE WING-E

A smart, rugged and flexible wellhead control solution designed for reliable operation in the most demanding environments.



KEY FEATURES



10" Color Multilanguage User Interface

Intuitive shutdown diagnostics and simple setup.



Integrated WebServer

Optional remote monitor & control.



Modbus Comm Port Standard

For remote monitoring and well shutdown requests.



WiFi Router (optional)

Wireless control via tablet / phone.



Graphical Trending

Flowline pressure trending.



Real Time Clock

Event logging on 32 GB microSD.



100% Electric Actuator Control

- Analog choke control
- Full open/close control for MV/SSV & WV's





PRESSURE RANGES

Actuator: Up to 3,000 PSI

Flow Line: Up to 10,000 PSI

*More ranges available upon request.



RUGGED DESIGN

- 24" x 24" x 12" Enclosure
- Painted CS or Optional SS316L
- NEMA 4 with safety keylocking door latches
- Internal Battery Backup for continuous operation



*Image for descriptive purposes only.

TYPICAL INSTALLATION



*Images for descriptive purposes only.



Installation

Designed for installation in unclassified location, ≥ 15 ft from wellhead per NFPA 497:2021, Fig. 5.10.2(a).



Power Supply

Universal Input 90-305 VAC, 50/60Hz for Customer provided Power Supply



Operating Temperature

-10°C to $+60^{\circ}\text{C}$ (14°F to 140°F)



Warranty

One year limited warranty.

USA / INDUSTRY, TX.
TEL +1 (979) 357-2243
sales@tracww.com